


- NOTES:**
- PANEL MAXIMUM WORKING PRESSURE - 15,000 PSI
 - NEEDLE VALVES RATED AT 20,000 PSI
 - BOOSTER RELIEF VALVE SET AT 8,250 PSI
 - CHOKE & KILL RELIEF VALVE SET AT 16,500 PSI
 - ALL BOTTOM CONNECTIONS ARE 1" MEDIUM PRESSURE RATED AT 20,000 PSI
 - 0-10,000 PSI GAUGE, 10" FACE
 - 12" CHART RECORDER, 0-10,000 PSI, 316 SS ENCLOSURE, 96 MINUTE ROTATION, WIND UP
 - ALL STAINLESS STEEL MATERIAL AND COMPONENTS
 - ALL COMPONENTS ARE FRONT MOUNTED FOR EASE OF SERVICE

PROPRIETARY AND CONFIDENTIAL:
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE SUBSEA COMPANY INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE SUBSEA COMPANY INC IS PROHIBITED.


3RD ANGLE PROJECTION:
 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5

WORKMANSHIP STANDARD PER WI 751-001

UNLESS OTHERWISE SPECIFIED:
 ALL DIMENSIONS ARE IN INCHES

WEIGHT: 1162.65 lbs.

| NAME | DATE |
|-----------------|---------|
| DRAWN: Green | 6-12-15 |
| CHECKED: Green | 6-12-15 |
| Q.A.: | |
| MFG./SALES: RJA | 6/12/15 |

| | | | | |
|---|--|--------------|---|-----------|
|  THE SUBSEA COMPANY INC | | SIZE | TITLE: | REV |
| | | B | BOOSTER LINE and CHOKE & KILL LINE TEST PANEL | A1 |
| DWG. NO. TSC-01581-GA | | SHEET 1 OF 1 | | |